



VRSC/V-Rod

Maintenance Schedule



ITEM SERVICED	PROCEDURE	MILEAGE						NOTES
		1,000	5,000	10,000	15,000	20,000	25,000	
Engine oil & filter	Replace		X	X	X	X	X	
Oil lines & brake system	Inspect for leaks	X	X	X	X	X	X	1
Air cleaner	Inspect, service as required	X	X	X	X	X	X	
Tires	Check pressure, inspect tread	X	X	X	X	X	X	
Clutch fluid	Check level & condition	X	X	X	X	X	X	
Rear belt & sprockets	Inspect, adjust belt	X	X	X	X	X	X	1
Throttle, brake, & clutch controls	Check, adjust & lubricate	X	X	X	X	X	X	1
Jiffy stand	Inspect & lubricate	X	X	X	X	X	X	1
Brake fluid	Check levels & condition	X	X	X	X	X	X	5
Brake pads and discs	Inspect for wear	X	X	X	X	X	X	
Spark plugs	Inspect		X		X		X	
	Replace			X		X		
Electrical equipment & switches	Check operation	X	X	X	X	X	X	
Front fork oil		Replace every 50,000 miles						1
Steering head bearings	Adjust	X				X		1, 2
Valve lash		Adjust valve lash every 15,000 miles						1, 4
Cooling system	Inspect; check clamps for tightness, check coolant freeze point	X		X		X		1
Coolant		Replace every 30,000 miles						1
Radiator	Clean	X	X	X	X	X	X	
Critical fasteners	Check tightness	X		X		X		1
Battery	Check battery & clean connections							3
Exhaust system	Inspect for leaks, cracks and loose or missing fasteners or heat shields	X	X	X	X	X	X	3
Road test	Verify component & system functions	X	X	X	X	X	X	

NOTES: 1. Should be performed by an authorized Harley-Davidson dealer, unless you have the proper tools, service data and are mechanically qualified. 2. Disassemble, lubricate and inspect every 30,000 miles. 3. Perform annually. 4. Could vary with frequency of operation and riding style. 5. Change D.O.T. 4 and flush brake system every two (2) years.